

M9000-3x0

LIT-1900237

Weather Shield Enclosures

Description

The M9000-3x0 Weather Shield Enclosures are cost-effective and durable weather shields designed to provide a degree of protection for a single Johnson Controls® M9000 Series Electric Actuator used in control damper, ball valve, and cast-iron flanged valve applications. These weather shield enclosures are manufactured to National Electrical Manufacturers' Association (NEMA) 3R specifications, and protect the electric actuator from corrosion, rain, freezing rain, sleet, and snow. The enclosure can be mounted indoors or outdoors; however, it may not prevent externally formed ice from restricting the motion of the rotary shaft.

Each enclosure is constructed of impact-grade ABS plastic that provides excellent impact resistance. The cover features ultraviolet inhibitors that extend service life by preventing the cover from becoming brittle or damaged by the sun or other environmental elements. The transparent cover provides an unobstructed view of the electric actuator without having to disassemble the enclosure. An appliance cord in the M9000-310 and M9000-330 Weather Shield Enclosure enables installation of control wiring, and a form-fitting seal prevents water or moisture from entering the unit and damaging the actuator.

Refer to the *M9000-3x0 Weather Shield Enclosures Product Bulletin (LIT-1201704)* for important product application information.

Features

- durable construction provides a degree of protection from the elements for a single Johnson Controls M9000 Series Electric Actuator used in control damper, ball valve, and iron-flanged valve applications
- fully enclosed NEMA 3R design protects the electric actuator from corrosion, rain, freezing rain, sleet, and snow
- impact-grade ABS plastic enclosure provides excellent impact resistance
- cover constructed using ultraviolet inhibitors extends service life by preventing the cover from becoming brittle or damaged by the sun or other environmental elements
- transparent cover allows the electric actuator to be fully viewable without having to disassemble the enclosure
- appliance cord enables installation of control wiring (M9000-310 and M9000-330 models)
- strain relief conduit fittings protect the electric actuator from damage by preventing tension on the electrical connection



M9000-3x0 Weather Shield Enclosures Shown Mounted onto a Control Damper, Flanged Ball Valve, Threaded Ball Valve, and Flanged Cast Iron Valve

Repair Information

If the M9000-3x0 Weather Shield Enclosure fails to operate within its specifications, replace the unit. For a replacement enclosure, contact the nearest Johnson Controls representative.

Selection Chart

Code Number	Description
M9000-310 ¹	Weather Shield Enclosure for a Single Johnson Controls M9106, M9108, M9109, M9116, M9124, and M9132 Series Electric Non-Spring Return Actuator Used in Control Damper and Iron Flanged Valve Applications
M9000-320 ¹	Weather Shield Enclosure for a Single Johnson Controls M9210 and M9220 Series Electric Spring Return Actuator Used in Control Damper and Iron Flanged Valve Applications
M9000-330 ¹	Weather Shield Enclosure for a Single Johnson Controls M9108, M9116, and M9124 Series Electric Non-Spring Return Actuator Used with VG1000 Series Ball Valves, 1/2 through 4 in.
M9000-340 ¹	Weather Shield Enclosure for a Single Johnson Controls M9210 and M9220 Series Electric Spring Return Actuator Used with VG1000 Series Ball Valves, 1/2 through 4 in.

1. Kit includes one enclosure base and seal assembly, one cover and gasket, and all necessary mounting hardware. One weather shield enclosure is required per electric actuator.

Technical Specifications

M9000-3x0 Weather Shield Enclosures		
Materials	Enclosure	Impact-Grade ABS Plastic
	Enclosure Seal	Nitrile
	Cover	Transparent Impact-Grade ABS Plastic with Ultraviolet Inhibitors
	Cover Gasket	Neoprene
Weather Shield Rating		NEMA 3R, IP54
Actuator Ambient Operating Temperature Limits	M9106 and M9109 (M9000-310 Only)	-4 to 125°F (-20 to 52°C)
	M9108, M9116, M9124, and M9132	-4 to 122°F (-20 to 50°C)
	M9210 and M9220	-40 to 131°F (-40 to 55°C)
Weather Shield Enclosure Ambient Storage Temperature Limits		-40 to 176°F (-40 to 80°C)
Electrical Connections		Strain Relief Conduit Fittings with 1/2 in. National Pipe Straight Mechanical (NPSM) Exit
Appliance Cord		6 Conductor, 18 AWG Wire Gauge, 43 in. (110 cm)
Shipping Weight	M9000-310	2.0 lb (0.9 kg)
	M9000-320	3.3 lb (1.5 kg)
	M9000-330	3.2 lb (1.45 kg)
	M9000-340	4.2 lb (1.9 kg)